



# Test Report : DKMW40G-15

---

40W 1"x1" Package DC-DC Regulated Converter

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

## ■ SAFETY TEST

Safety Test

## ■ RELIABILITY TEST

Environment Test

**DESIGN VERIFY TEST**
**OUTPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-1.0% ~ +1.0 %	I/P:48VDC O/P:FULL LOAD Ta:25°C	V1:+0.31% V2:+0.39%	P
2	RIPPLE & NOISE	75 mVp-p	I/P:48VDC O/P:FULL LOAD Ta:25°C	V1:19mV V2:18mV	P
3	LINE REGULATION	-0.5% ~ +0.5%	I/P:18VDC~75VDC O/P:FULL LOAD Ta:25°C	V1:-0.09% ~ +0.03% V2:+0.09% ~ -0.03%	P
4	LOAD REGULATION	-1.0% ~ +1.0%	I/P:48VDC O/P:0% LOAD~FULL LOAD Ta:25°C	V1:+0.03% ~ +0.05% V2:+0.03% ~ +0.03%	P

**INPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	EFFICIENCY	88%	I/P:48VDC O/P:FULL LOAD Ta:25°C	88.44%	P
2	DC CURRENT	940 mA / FULL LOAD 10 mA / NO LOAD	I/P:48VDC O/P:NO / FULL LOAD Ta:25°C	933mA / FULL LOAD 5.4mA / NO LOAD	P
3	START UP TIME	30 ms max.	I/P:48VDC O/P:FULL LOAD Ta:25°C	V1:21.0mS V2:20.0mS	P

**PROTECTION FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	SHORT PROTECTION	CONTINUOUS	I/P:75VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE AUTO-RECOVER	P
2	OVER LOAD PROTECTION	110~200%	I/P:48VDC O/P:TESTING Ta:25°C	174.93 % HICCUP MODE AUTO-RECOVER	P
3.	OVER VOLTAGE PROTECTION	YES	I/P:TESTING O/P:FULL LOAD Ta:25°C	Clamp by Zener diode	P
4	OVER TEMPERATURE PROTECTION	+110°C THERMAL SHUTDOWN	I/P:48VDC O/P:TESTING Ta: TESTING	OK AUTOMATIC RECOVERY	P
5	UNDER VOLTAGE LOCKOUT	START-UP 17.5V SHUTDOWN VOLTAGE 17V	I/P:TESTING O/P:FULL LOAD Ta:25°C	17.17VDC 16.61VDC	P

## CONTROL FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	REMOTE CONTROL	Power on : R.C. ~ - Vin>3.5~12Vdc or open circuit Power off : R.C. ~ - Vin <1.2Vdc or short	I/P:48VDC O/P:FULL LOAD Ta:25°C	Power on : R.C>3.0Vdc or Open Power off : R.C<1.2Vdc or short	P

## ■ SAFETY TEST

### SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:2K VDC/min	I/P-O/P:2K VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

## ■ RELIABILITY TEST

### ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT										
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:48VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 4HRS I/P:48VDC O/P:FULL LOAD Ta=30°C 3. HIGH AMBIENT BURN-IN : 4HRS I/P:48VDC O/P:50% LOAD Ta=60°C			P										
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> <th>3</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>103.9°C</td> <td>108.9°C</td> <td>106.7°C</td> </tr> </tbody> </table>			NO	Position	1	2	3	1	CASE	103.9°C	108.9°C	106.7°C	
NO	Position	1	2	3											
1	CASE	103.9°C	108.9°C	106.7°C											
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 4 HOURS	I/P:48VDC O/P: FULL LOAD Ta= -40°C	TEST : OK	P										

## OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 1.785714 M.T.B.F : 560K HRS			P

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN HSIAO	PETER CHENG