



Test Report: HLG-80H-15

80W Constant Voltage + Constant Current LED Driver

■ DESIGN VERIFY TEST

Output Function Test
Input Function Test
Protection Function Test
Control Function Test
Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test
E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	CONSTANT CURRENT REGION	9V-15V	I/P : 230VAC O/P : CV=9V-14V Ta : 25°C	TEST : OK
2	RIPPLE & NOISE	V1 : 150 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 19.4 mVp-p (Max)
3	OUTPUT VOLTAGE ADJUST RANGE	CH1 : 13.5V ~ 17 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	13.096 V ~ 17.496 V / 230 VAC 13.101 V ~ 17.496 V / 115 VAC
4	CURRENT ADJUST RANGE	CH1 : 3A ~ 5A	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	1.009 A ~ 5.676 A / 230 VAC 1.008 A ~ 5.699 A / 115 VAC
5	OUTPUT VOLTAGE TOLERANCE	V1 : 2 % ~ -2 % (Max)	I/P : 100 VAC / 305 VAC O/P : FULL / MIN LOAD Ta : 25°C	V1 : 0.32 % ~ -0.32 %
6	LINE REGULATION	V1 : 0.5 % ~ -0.5 % (Max)	I/P : 100VAC ~ 305 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0 % ~ 0 %
67	LOAD REGULATION	V1 : 1.5 % ~ -1.5 % (Max)	I/P : 230 VAC O/P : FULL -MIN LOAD Ta : 25°C	V1 : 0.4 % ~ -0.4 %
8	SET UP TIME	230VAC : 500 ms (Max) 115VAC : 1200 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 294 ms 115VAC/ 330 ms
9	RISE TIME	230VAC : 200 ms (Max) 115VAC : 200 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 19 ms 115VAC/ 16 ms
10	HOLD UP TIME	230VAC : 16 ms (TYP) 115VAC : 16 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 89 ms 115VAC/ 38 ms
11	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : <5 %
12	DYNAMIC LOAD	V1 : 1500 mVp-p	I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1)215 mVp-p (2)502 mVp-p

13	DIMMER TEST (for B-type only)	SPEC:																																
		*Reference resistance value for output current adjustment (Typical)																																
		<table border="1"> <tr> <th>Resistance value</th> <th>10K</th> <th>20K</th> <th>30K</th> <th>40K</th> <th>50K</th> <th>60K</th> <th>70K</th> <th>80K</th> <th>90K</th> <th>100K</th> </tr> <tr> <th>Output current</th> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> </tr> </table>	Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%										
		Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K																						
		Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																						
		*1 ~ 10V dimming function for output current adjustment (Typical)																																
		<table border="1"> <tr> <th>Dimming value</th> <th>1V</th> <th>2V</th> <th>3V</th> <th>4V</th> <th>5V</th> <th>6V</th> <th>7V</th> <th>8V</th> <th>9V</th> <th>10V</th> </tr> <tr> <th>Output current</th> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> </tr> </table>	Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%										
		Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V																						
		Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																						
		*10V PWM signal for output current adjustment (Typical)																																
		<table border="1"> <tr> <th>Duty value</th> <th>10%</th> <th>20%</th> <th>30%</th> <th>40%</th> <th>50%</th> <th>60%</th> <th>70%</th> <th>80%</th> <th>90%</th> <th>100%</th> </tr> <tr> <th>Output current</th> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> </tr> </table>	Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%										
		Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																						
		Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																						
TEST RESULT: I/P : 230 VAC ; Ta : 25°C																																		
<table border="1"> <tr> <th rowspan="3">1</th> <th>Resistance value</th> <th>10K</th> <th>20K</th> <th>30K</th> <th>40K</th> <th>50K</th> <th>60K</th> <th>70K</th> <th>80K</th> <th>90K</th> <th>100K</th> </tr> <tr> <th>Output current</th> <td>0.653A</td> <td>0.990A</td> <td>1.527A</td> <td>2.026A</td> <td>2.519A</td> <td>2.971A</td> <td>3.428A</td> <td>3.906A</td> <td>4.437A</td> <td>4.924A</td> </tr> <tr> <th>%</th> <td>13.06%</td> <td>19.80%</td> <td>30.54%</td> <td>40.52%</td> <td>50.38%</td> <td>59.42%</td> <td>68.56%</td> <td>78.12%</td> <td>88.74%</td> <td>98.48%</td> </tr> </table>	1	Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	Output current	0.653A	0.990A	1.527A	2.026A	2.519A	2.971A	3.428A	3.906A	4.437A	4.924A	%	13.06%	19.80%	30.54%	40.52%	50.38%	59.42%	68.56%	78.12%	88.74%	98.48%
1		Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K																						
		Output current	0.653A	0.990A	1.527A	2.026A	2.519A	2.971A	3.428A	3.906A	4.437A	4.924A																						
	%	13.06%	19.80%	30.54%	40.52%	50.38%	59.42%	68.56%	78.12%	88.74%	98.48%																							
<table border="1"> <tr> <th rowspan="3">2</th> <th>Dimming value</th> <th>1V</th> <th>2V</th> <th>3V</th> <th>4V</th> <th>5V</th> <th>6V</th> <th>7V</th> <th>8V</th> <th>9V</th> <th>10V</th> </tr> <tr> <th>Output current</th> <td>0.654A</td> <td>0.992A</td> <td>1.518A</td> <td>2.033A</td> <td>2.518A</td> <td>3.008A</td> <td>3.499A</td> <td>3.998A</td> <td>4.510A</td> <td>5.025A</td> </tr> <tr> <th>%</th> <td>13.08%</td> <td>19.84%</td> <td>30.36%</td> <td>40.66%</td> <td>50.36%</td> <td>60.16%</td> <td>69.98%</td> <td>79.96%</td> <td>90.20%</td> <td>100.50%</td> </tr> </table>	2	Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	Output current	0.654A	0.992A	1.518A	2.033A	2.518A	3.008A	3.499A	3.998A	4.510A	5.025A	%	13.08%	19.84%	30.36%	40.66%	50.36%	60.16%	69.98%	79.96%	90.20%	100.50%
2		Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V																						
		Output current	0.654A	0.992A	1.518A	2.033A	2.518A	3.008A	3.499A	3.998A	4.510A	5.025A																						
	%	13.08%	19.84%	30.36%	40.66%	50.36%	60.16%	69.98%	79.96%	90.20%	100.50%																							
<table border="1"> <tr> <th rowspan="3">3</th> <th>Duty value</th> <th>10%</th> <th>20%</th> <th>30%</th> <th>40%</th> <th>50%</th> <th>60%</th> <th>70%</th> <th>80%</th> <th>90%</th> <th>100%</th> </tr> <tr> <th>Output current</th> <td>0.543A</td> <td>0.932A</td> <td>1.440A</td> <td>1.993A</td> <td>2.507A</td> <td>3.017A</td> <td>3.533A</td> <td>4.057A</td> <td>4.587A</td> <td>5.126A</td> </tr> <tr> <th>%</th> <td>10.86%</td> <td>18.64%</td> <td>28.80%</td> <td>39.86%</td> <td>50.14%</td> <td>60.34%</td> <td>70.66%</td> <td>81.14%</td> <td>91.74%</td> <td>102.52%</td> </tr> </table>	3	Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Output current	0.543A	0.932A	1.440A	1.993A	2.507A	3.017A	3.533A	4.057A	4.587A	5.126A	%	10.86%	18.64%	28.80%	39.86%	50.14%	60.34%	70.66%	81.14%	91.74%	102.52%
3		Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																						
		Output current	0.543A	0.932A	1.440A	1.993A	2.507A	3.017A	3.533A	4.057A	4.587A	5.126A																						
	%	10.86%	18.64%	28.80%	39.86%	50.14%	60.34%	70.66%	81.14%	91.74%	102.52%																							

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	90VAC~305 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C I/P : LOW-LINE=3V= 87 V HIGH-LINE=305 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	70 V~305V TEST : OK
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE	I/P : 90 VAC ~ 305 VAC O/P : FULL -MIN LOAD Ta : 25°C	TEST : OK
3	POWER FACTOR	0.96 / 230 VAC(TYP) 0.96 / 115 VAC(TYP) 0.94 / 277 VAC(TYP)	I/P : 230 VAC I/P : 115 VAC I/P : 277 VAC O/P : FULL LOAD Ta : 25°C	PF= 0.964 / 230 VAC PF= 0.991 / 115 VAC PF= 0.945 / 277 VAC
4	EFFICIENCY	89 % (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	90.31 %

5	INPUT CURRENT	277V/ 0.4 A (TYP) 230V/ 0.425 A (TYP) 115V/ 0.85 A (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 0.32 A/ 277VAC I = 0.37 A/ 230 VAC I = 0.73 A/ 115 VAC
6	INRUSH CURRENT	230V/ 70 A (TYP) COLD START	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I = 63 A/ 230 VAC
7	LEAKAGE CURRENT	< 0.75 mA / 277 VAC	I/P : 277 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.2 mA N-FG : 0.2 mA
8	TOTAL HARMONIC DISTORTION	THD < 20% when output loading ≥ 60% at 115VAC/230VAC input and output loading ≥ 75% at 277VAC input	I/P : 115 VAC I/P : 230 VAC O/P : 60% LOAD I/P : 277 VAC O/P : 75%LOAD Ta : 25°C	THD : 11.3 /115VAC THD : 17.4 /230VAC THD : 17.28 /277VAC

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER LOAD PROTECTION	95 % ~ 108 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	100.9 %/ 230 VAC 101 %/ 115 VAC Constant current limiting, recovers automatically after fault condition is removed
2	OVER VOLTAGE PROTECTION	CH1 : 18 V ~ 24 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	19.222 V/ 230 VAC 19.178 V/ 115 VAC Shut down o/p voltage, re-power on to recover
3	OVER TEMPERATURE PROTECTION	NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage, re-power on to recover
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 305 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE HICCUP

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q 1 Rated : 12A/700V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 628 V (2) 512 V (3) 624 V
2	Diode Peak Voltage	Q101 Rated : 80A/75V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 74.4 V (2) 72.8 V (3) 57.2 V
3	Clamp Diode Peak Voltage	D12 Rated : GP20K	I/P : High-Line +3V = 308 V O/P : (1) Dynamic Load 90%Duty/1KHz (2)Full load continue Ta : 25°C	(1) 600 V (2) 596 V
4	Input Capacitor Voltage	C 5 Rated : 82u/450V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 422.87 V (2) 434.37 V (3) 434.29 V
5	Control IC Voltage Test	U1 Rated : 16V~38V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 21.687 V (2) 21.516 V (3) 21.523 V
6	Power Transistor (D to S) or (C to E) Peak Voltage	Q2 Rated : 10A/600V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 500 V (2) 456 V (3) 460 V

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P : 3.75 KVAC/min I/P-FG : 2 KVAC/min<4.5mA O/P-FG : 1.5 KVAC/min	I/P-O/P : 4 KVAC/min I/P-FG : 2.4KVAC/min O/P-FG : 1.8 KVAC/min Ta : 25°C	I/P-O/P : 2.197 mA I/P-FG : 2.172 mA O/P-FG : 0.433 mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C /70%RH	I/P-O/P : 30 GΩ I/P-FG : 30 GΩ O/P-FG : 30 GΩ NO DAMAGE
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	9 mΩ
4	APPROVAL	TUV : Certificate NO : R50202516 UL : File NO : E334687		

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	HARMONIC	EN61000-3-2 CLASS C	I/P: 230VAC/50HZ O/P:100% ELECTRONICLOAD O/P:100%LED LOAD Ta:25°C	PASS
2	CONDUCTION	EN55015 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab
3	RADIATION	EN55015 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab
4	E.S.D	EN61000-4-2 INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA B
5	E.F.T	EN61000-4-4 INDUSTRY INPUT: 2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA B
6	SURGE	IEC61000-4-5 INDUSTRY L-N :2KV L,N-PE:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA B
7	Test by certified Lab & Test Report Prepare. Any contradictions of the test results, please refer to the latest EMC test report.			

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																				
1	TEMPERATURE RISE TEST	MODEL : HLG-80H-12 1. ROOM AMBIENT BURN-IN : 13.5 HRS I/P : 230VAC O/P : 95% LOAD Ta=25.1℃ 2. HIGH AMBIENT BURN-IN : 67 HRS I/P : 230VAC O/P : 95% LOAD Ta=63.8℃	<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 25.1 ℃</th> <th>HIGH AMBIENT Ta=63.8 ℃</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>44.9℃</td><td>77.0℃</td></tr> <tr><td>2</td><td>BD1</td><td>49.3℃</td><td>81.2℃</td></tr> <tr><td>3</td><td>L1</td><td>48.4℃</td><td>79.8℃</td></tr> <tr><td>4</td><td>C5</td><td>48.4℃</td><td>79.8℃</td></tr> <tr><td>5</td><td>Q1</td><td>52.2℃</td><td>84.1℃</td></tr> <tr><td>6</td><td>Q2</td><td>49.9℃</td><td>81.8℃</td></tr> <tr><td>7</td><td>U1</td><td>46.4℃</td><td>78.4℃</td></tr> <tr><td>8</td><td>RTH2</td><td>47.0℃</td><td>78.7℃</td></tr> <tr><td>9</td><td>T1</td><td>52.6℃</td><td>84.0℃</td></tr> <tr><td>10</td><td>Q101</td><td>51.1℃</td><td>83.6℃</td></tr> <tr><td>11</td><td>C106</td><td>49.3℃</td><td>81.3℃</td></tr> <tr><td>12</td><td>L100</td><td>47.2℃</td><td>79.5℃</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 25.1 ℃	HIGH AMBIENT Ta=63.8 ℃	1	LF1	44.9℃	77.0℃	2	BD1	49.3℃	81.2℃	3	L1	48.4℃	79.8℃	4	C5	48.4℃	79.8℃	5	Q1	52.2℃	84.1℃	6	Q2	49.9℃	81.8℃	7	U1	46.4℃	78.4℃	8	RTH2	47.0℃	78.7℃	9	T1	52.6℃	84.0℃	10	Q101	51.1℃	83.6℃	11	C106	49.3℃	81.3℃	12	L100	47.2℃	79.5℃	
NO	Position	ROOM AMBIENT Ta= 25.1 ℃	HIGH AMBIENT Ta=63.8 ℃																																																					
1	LF1	44.9℃	77.0℃																																																					
2	BD1	49.3℃	81.2℃																																																					
3	L1	48.4℃	79.8℃																																																					
4	C5	48.4℃	79.8℃																																																					
5	Q1	52.2℃	84.1℃																																																					
6	Q2	49.9℃	81.8℃																																																					
7	U1	46.4℃	78.4℃																																																					
8	RTH2	47.0℃	78.7℃																																																					
9	T1	52.6℃	84.0℃																																																					
10	Q101	51.1℃	83.6℃																																																					
11	C106	49.3℃	81.3℃																																																					
12	L100	47.2℃	79.5℃																																																					
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 305VAC/100VAC O/P : 95% LOAD Ta= -40℃ / -25	TEST : OK																																																				
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60 ℃ NO DAMAGE	I/P : 305 VAC O/P : 95% LOAD Ta= 60 ℃ HUMIDITY= 95 %R.H	TEST : OK																																																				
4	TEMPERATURE COEFFICIENT	± 0.03 % (0-50℃)	I/P : 230 VAC O/P : 95% LOAD	± 0.02 % (0-50℃)																																																				
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45℃~ +90℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK																																																				
6	THERMAL SHOCK TEST	1. Thermal shock Temperature : -40℃~ +65℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec		OK																																																				

7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10-500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 5G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C	TEST : OK
8	CAPACITOR LIFE CYCLE	HLG-80H-12 :SUPPOSE C106 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Tc=75 °C LIFE TIME (2) I/P : 230VAC O/P : 75% LOAD Tc= 75 °C LIFE TIME (3) I/P : 230VAC O/P : 50% LOAD Tc= 75 °C LIFE TIME	(1) 63406 HRS (2) 74939 HRS (3) 91150 HRS
9	MTBF	Conducted by Parts Stress Analysis Prediction 357.8K hrs min. MIL-HDBK-217F (25°C)	
10	Ongoing Reliability Test	I/P : 230VAC O/P : FULL LOAD TA=50°C Demonstration Mean Time Between Failure : 62,000 hours	

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	DANIEL GAO	SANFORD SU	VINCENT TSENG

2009/08/04 A50-F023