



MODEL : NSD10-12D12

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 75 mVp-p (Max) V2: 75 mVp-p (Max)	I/P: 12VDC O/P:FULL LOAD Ta:25°C	V1: 14 mVp-p (Max) V2: 14 mVp-p (Max)	P
2	OUTPUT VOLTAGE TOLERANCE	V1: 2 %- -2 % (Max) V2: 2 %- -2 % (Max)	I/P: 9.8VDC / 36VDC O/P:FULL/ MIN LOAD Ta:25°C	V1: 1.2 %- -1.2 % V2: 1.2 %- -1.2 %	P
3	LINE REGULATION	V1: 1%- -1 % (Max) V2: 1%- -1% (Max)	I/P: 9.8VDC ~ 36VDC O/P:FULL LOAD Ta:25°C	V1: 0 %- 0 % V2: 0 %- 0 %	P
4	LOAD REGULATION	V1: 2 %- -2 % (Max) V2: 2 %- -2 % (Max)	I/P: 12VDC O/P:FULL -MIN LOAD Ta:25°C	V1: 0 %- 0 % V2: 0.05 %- -0.05 %	P
5	CROSS REGULATION	V1: 2 %- -2 % (Max) V2: 2 %- -2 % (Max)	I/P: 12V VDC O/P: Testing O/P 60%LOAD Other O/P 40%LOAD Change Ta:25°C	V1: 1 %- -1 % V2: 0.9 %- -0.9 %	P
6	OVER/UNDERSHOOT TEST	< ±5%	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	TEST: < 5 %	P
7	DYNAMIC LOAD	V1: 1200 mVp-p	I/P: 12VDC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	137 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	9.8VDC~ 36 VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	8.6 V~ 36 V	P
			I/P: LOW-LINE-0.2V= 9.6 V HIGH-LINE+5%= 37.8 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	EFFICIENCY	77 % (TYP)	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	78 %	P
3	INPUT CURRENT	12 VDC/ 1.4A(TYP)	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	I = 1.06 A	P
4	SHUTDOWN IDLE CURRENT	20 mA / 12VDC	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	18.1 mA / 12VDC	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	Above 105%	I/P: 12VDC O/P: TESTING Ta: 25°C	165 % / 12V Over power Limiting, recovers automatically after fault condition is removed	P
2	OVER VOLTAGE PROTECTION	CH1: 13.8 V~ 18V CH2: -13.8 V~ -18V	I/P: DC SOURCE O/P: MIN LOAD Ta: 25°C	14.8 V / CH1 / 0.32A 14.8V / CH2 / 0.32A Recovers automatically after fault condition is removed	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 60 SECOND NO DAMAGE	I/P: 36 VDC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Constant Current Limiting	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Logic "1" OPEN : ON Logic "0" GON : OFF	I/P: 12VDC O/P: FULL LOAD Ta: 25°C	Logic "1" : POWER ON Logic "0" : POWER OFF	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	TEMPERATURE RISE TEST	MODEL : NSD10-12D5 1. ROOM AMBIENT BURN-IN : 1.5 HRS I/P: 12 VDC O/P: FULL LOAD Ta= 25.1℃ 2. HIGH AMBIENT BURN-IN : 2HRS I/P: 12 VDC O/P: FULL LOAD Ta= 58.2 ℃			P
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 12VDC O/P: 120 % LOAD Ta:25℃	TEST : OK	P
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 12 VDC O/P: 100 % LOAD Ta= -25℃	TEST : OK	P
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60 ℃ NO DAMAGE	I/P: 39 VDC O/P:FULL LOAD Ta= 60℃ HUMIDITY= 95 %R.H	TEST : OK	P
5	TEMPERATURE COEFFICIENT	± 0.03 %(0-60℃)	I/P: 12 VDC O/P:FULL LOAD	± 0.006 %(0-60℃)	P
6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10-500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25℃		TEST : OK	P

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 1.5KVDC/min	I/P-O/P: 1.8KVDC/min Ta:25℃	I/P-O/P: 0.002 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P: 500 VDC Ta:25℃ / 70% RH	I/P-O/P: 30 GΩ NO DAMAGE	P
3	APPROVAL	TUV: Certificate NO : UL: File NO : E183223			P



E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RADIATION	EN55022 CLASS B	I/P: 12VDC O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab	P
2	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR: 8KV / Contact: 4KV	I/P: 12 VDC O/P: FULL LOAD Ta: 25°C	CRITERIA A	P
3	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 12 VDC O/P: FULL LOAD Ta: 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 1878.5K HRS			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q2 Rated CUE1012 : 120 V 10 A	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on (2) Output Short Ta: 25°C	(1) 74 V (2) 84 V	P
2	Diode Peak Voltage	D100 Rated EC11FS2-TE12L 1A/200V D200 Rated EC11FS2-TE12L 1A/200V	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on (2) Output Short Ta: 25°C	(1) 154 V (2) 91 V (1) 156 V (2) 89 V	P
3	Input Capacitor Voltage	C5 Rated : 105 / 50V	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on /Off (2) Min load Turn on /Off (3) Full Load /Min load Change Ta: 25°C	(1) 38.96 V (2) 39 V (3) 39 V	P
4	Control IC Voltage Test	U1 Rated TL3843D : 20 V	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on /Off (2) Min load Turn on /Off (3) Full Load /Min load Change Ta: 25°C	(1) 14.92 V (2) 11.31 V (3) 14.92 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2007/1/11	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2007/3/5	PRODUCT SAMPLE W0702A48	PASS	VINCENT TSENG	MAX LIN

2003/12/12 A50-F023