



Test Report : SMU02N-15N

2W DC-DC Unregulated Single output Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety test

■ RELIABILITY TEST

Environment Test

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

| NO | TEST ITEM | SPECICATION | TEST CONDITION | RESULT | VERDICT |
|----|------------------|----------------------|---|-------------------|---------|
| 1 | VOLTAGE ACCURACY | -3.0% ~ +3.0 % (Max) | I/P:24VDC O/P:FULL LOAD Ta:25°C | -0.85% | P |
| 2 | RIPPLE & NOISE | 100 mVp-p (Max) | I/P:26.4VDC O/P:FULL LOAD Ta:25°C | 16 mV | P |
| 3 | LINE REGULATION | -12% ~ +12 % | I/P:21.6VDC~26.4VDC O/P:FULL LOAD Ta:25°C | -10.47% ~ +10.51% | P |
| 4 | LOAD REGULATION | -8.0% ~ +8.0% | I/P:24VDC O/P:10% LOAD~FULL LOAD Ta:25°C | -0.94% ~ +1.00% | P |

INPUT FUNCTION TEST

| NO | TEST ITEM | SPECICATION | TEST CONDITION | RESULT | VERDICT |
|----|------------|-------------------------------------|--|---------------------------------------|---------|
| 1 | EFFICIENCY | 88% | I/P:24VDC O/P:FULL LOAD Ta:25°C | 89.63% | P |
| 2 | DC CURRENT | 95 mA / FULL LOAD 6 mA / NO LOAD | I/P:24VDC O/P:NO / FULL LOAD Ta:25°C | 91 mA / FULL LOAD 4.6 mA / NO LOAD | P |

PROTECTION FUNCTION TEST

| NO | TEST ITEM | SPECICATION | TEST CONDITION | RESULT | VERDICT |
|----|------------------|-------------|---|-----------------------------------|---------|
| 1 | SHORT PROTECTION | CONTINUOUS | I/P:26.4VDC O/P:FULL LOAD Ta:25°C | CONTINUOUS, AUTOMATIC RECOVERY | P |
| 2 | CASE TEMPERATURE | +115°C max | I/P:24VDC O/P:TESTING Ta: TESTING | OK AUTOMATIC RECOVERY | P |

SAFETY TEST
SAFETY TEST

| NO | TEST ITEM | SPECICATION | TEST CONDITION | RESULT | VERDICT |
|----|----------------------|----------------------|---------------------------------|-------------------------------|---------|
| 1 | WITHSTAND VOLTAGE | I/P-O/P:1500 VDC/min | I/P-O/P:1500 VDC/min Ta:25°C | I/P-O/P: 0.002mA NO DAMAGE | P |
| 2 | ISOLATION RESISTANCE | I/P-O/P:500VDC>100MΩ | I/P-O/P:500 VDC Ta:25°C | I/P-O/P>100MΩ NO DAMAGE | P |

■ RELIABILITY TEST

ENVIRONMENT TEST

| NO | TEST ITEM | SPECICATION | TEST CONDITION | RESULT | | | | | | | | | | |
|----|------------------------------|--|--|-----------|----|----------|---|---|---|---|------|--------|--------|---------|
| 1 | TEMPERATURE RISE TEST | 1. ROOM AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:FULL LOAD Ta=85°C 3. HIGH AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:60% LOAD Ta=105°C | | | | | | | | | | | | |
| | | <table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> <th>3</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>38.5°C</td> <td>94.7°C</td> <td>111.6°C</td> </tr> </tbody> </table> | | | NO | Position | 1 | 2 | 3 | 1 | CASE | 38.5°C | 94.7°C | 111.6°C |
| NO | Position | 1 | 2 | 3 | | | | | | | | | | |
| 1 | CASE | 38.5°C | 94.7°C | 111.6°C | | | | | | | | | | |
| 2 | LOW TEMPERATURE TURN ON TEST | TURN ON AFTER 4 HOURS | I/P:24VDC O/P: FULL LOAD Ta= -40°C | TEST : OK | | | | | | | | | | |

OTHER

| NO | TEST ITEM | SPECICATION | TEST CONDITION | RESULT |
|----|-----------|--|----------------|--------|
| 1 | MTBF | MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 0.5 M.T.B.F : 2,000KHRS | | |

| TEST RESULT | TESTER | APPROVAL |
|-------------|--------------|-------------|
| PASS | ARCHEN HSIAO | PETER CHENG |